



TOUGHLAC™ Hide and Seal
Shellac Based Sanding Sealer



Kane International Corporation
 411 Theodore Fremd Ave Ste 106
 Rye, NY, 10580
 tel 914-921-3100 800-323-8946 fax 914-921-3180
 www.toughlac.com info@toughlac.com

The Most Effective Wood Sealer on the Market

Test Results PASS FAIL

| G = Gummy Test A = Appearance Test | | Test 1 | Test 2 | Test 3 |
|---------------------------------------|---|---|-------------------------------------|---|
| | | Sand - Seal - Sand - Stain 1/2 - Topcoat 1/4 | Sand - Seal - Sand - Topcoat 1/2 | Sand - Seal -Sand -Seal 3/4 -Sand - Seal 1/2 - Sand - Topcoat 1/4 |
| Toughlac™ Hide & Seal | G | | | |
| | A | | | |
| National Brand 1 | G | | | |
| | A | | | |
| National Brand 2 | G | | | |
| | A | | | |
| National Brand 3 | G | | | |
| | A | | | |
| National Brand 4 | G | | | |
| | A | | | |
| National Brand 5 | G | | | |
| | A | | | |
| National Brand 6 | G | | | |
| | A | | | |

Appearance - "PASS" Requires Smooth Surface and Gloss Readings of 50 or higher for Oak, Pine, AND Cedar Substrates

Gumming - "PASS" Requires Absolutely No Gumming after Sanding Test

Test Results Available Upon Request

Benefits Include:

- Dust Free in 10 Minutes
- Recoat in 1 Hour
- Adds a Natural Tone to Wood Surfaces
- Does Not Yellow
- Will Not Raise Grain
- When Sanded, Will Not Gum the Sandpaper
- Permanently Seals in and Blocks Odors from Mold, Mildew, Pets, Smoke, and others
- When Dry, Resists Water and Solvents
- VOC Compliant - 533 Grams/Liter
- Requires Fewer Layers to Topcoat
- Permits Staining to be Even and Uniform
- 100% Wax Free
- Can Be Top Coated with Any Solvent-Based or Waterborne Finish Coat
- Better Than Other Sealers – Higher Gloss, Fewer Surface Defects, and No Gumming of Sandpaper